

FEBRUARY 2017



Bismuth

Product

Heavy, lustrous silver-white metal with pink tinge. Crystalline with a brittle grain structure. Available in Ingot and granulated form.

Applications

Alloying in metals - in particular fusible (low-melt) alloys.

As a replacement for lead shot.

Pharmaceutical applications.

Specification

Purity:	99.99% pure
Melting Point:	271°C
Specific Gravity:	9.8gm per cc
Form:	Slab 13Kg approx
Size:	140mm x 310mm x 30mm
Chemical Symbol:	Bi

THIS DATA SHEET IS OFFERED SOLELY FOR YOUR INFORMATION, CONSIDERATION AND INVESTIGATION. CAGROUP PROVIDES NO WARRANTIES, EITHER EXPRESSED OR IMPLIED AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THE DATA CONTAINED HEREIN. MATERIAL USE BEYOND THE CONTROL OF SUPPLIER

MELBOURNE (Head Office):
32 Industrial Avenue.
Thomastown, Vic. 3074
Telephone: (03) 8301 7100
Facsimile: (03) 9359 4076

SYDNEY:
5 Coates Place,
Wetherill Park, N.S.W. 2164
Telephone: (02) 8795 6300
Facsimile: (02) 9756 4074

BRISBANE:
62 Parramatta Road,
Underwood, Qld. 4119
Telephone: (07) 3086 7300
Facsimile: (07) 3209 3611

PERTH:
Unit 10, 305 Victoria Road
Malaga, W.A. 6090
Telephone: (08) 9207 9300
Facsimile: (08) 9248 9543