

TDS of Builders film

Date Issued: 23.01.2025

Description: Low Density Builders Film

Application: Building/Construction Industry

Standard: AS2870:2011 – Residential Slabs and Footings

Product Composition

100% recycling of LDPE and LLDPE

LLDPE Melt Flow Index: 2.2-2.5 gm/min

Polymer String Value: 300

Product Dimensions: Length: 50m, Width: 2m, 4m, and Thickness: 200 ± 20µm

Technical Specification

Impact: Medium

Appearance: Black

Test Specification: AS 2870 – 2011 clause 5.3.3.3 (a) & (b)

Reference Methods: (i) AS/NZS 4347.6:1995 – Damp-proof Course and Flashings; Method 6
– Determining Impact Resistance (Falling Dart Impact Test)

(ii) AS/NZS 4347.9:1995 Method 9 – Determination of thickness

Product Destination

Slab on ground construction, industrial applications, asbestos removal, liner for bins and dams, floor protection.

Safety: Material is asbestos, tar compounds and dangerous substances free. NON-HAZARDOUS CHEMICAL According to the WHS Regulations and the ADG Code.

Storage: Material is packed Horizontally on pallet. Keep horizontally in the warehouse. Keep away from heat sources.

Other: The producer can update the TDS without notice.
