



FEBRUARY 2017

Cadmium

Product

Soft silver-white metal, malleable and toxic.

Applications

Used for alloying in fusible (low-melt) alloys, jewellery casting alloys and brazing alloys.
Also used in electroplating and cathodic protection applications, as well as a stabilizer in plastics.

Specification

Purity: 99.99% pure
Melting Point: 320°C
Specific Gravity: 8.65gm per cc
Form: Ball form only
Size: 50mm diameter, 570gm each
Chemical Symbol: Cd

THIS DATA SHEET IS OFFERED SOLELY FOR YOUR INFORMATION, CONSIDERATION AND INVESTIGATION. CAGROUP PROVIDES NO WARRANTIES, EITHER EXPRESSED OR IMPLIED AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THE DATA CONTAINED HEREIN. MATERIAL USE BEYOND THE CONTROL OF SUPPLIER

MELBOURNE (Head Office):
32 Industrial Avenue.
Thomastown, Vic. 3074
Telephone: (03) 8301 7100
Facsimile: (03) 9359 4076

SYDNEY:
5 Coates Place,
Wetherill Park, N.S.W. 2164
Telephone: (02) 8795 6300
Facsimile: (02) 9756 4074

BRISBANE:
62 Parramatta Road,
Underwood, Qld. 4119
Telephone: (07) 3086 7300
Facsimile: (07) 3209 3611

PERTH:
Unit 10, 305 Victoria Road
Malaga, W.A. 6090
Telephone: (08) 9207 9300
Facsimile: (08) 9248 9543