

FEBRUARY 2017



Sheet Lead (Up to 25kg)

Product Description

CA manufacture a large range of soft Lead sheeting by Direct Method (DM)
Sheet lead is manufactured to AS1804-1976

Application

Used for Roofs, Flashings, Weathering, Damp Proofing, Sound Attenuation, Chemical Plants and other uses.

Form

Available in the following standard widths

150mm
225mm
300mm
450mm
600mm
900mm
1220mm

In 3 or 6 metre rolls

Also available in 450 & 600 squares

Thickness:

Available in 5kg (0.44mm), 10kg (0.88mm), 15kg (1.32mm) 20kg (1.76mm) & 25kg (2.2mm)

THIS DATA SHEET IS OFFERED SOLELY FOR YOUR INFORMATION, CONSIDERATION AND INVESTIGATION. CAGROUP PROVIDES NO WARRANTIES, EITHER EXPRESSED OR IMPLIED AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THE DATA CONTAINED HEREIN. MATERIAL USE BEYOND THE CONTROL OF SUPPLIER

MELBOURNE (Head Office):
32 Industrial Avenue.
Thomastown, Vic. 3074
Telephone: (03) 8301 7100
Facsimile: (03) 9359 4076

SYDNEY:
5 Coates Place,
Wetherill Park, N.S.W. 2164
Telephone: (02) 8795 6300
Facsimile: (02) 9756 4074

BRISBANE:
62 Parramatta Road,
Underwood, Qld. 4119
Telephone: (07) 3086 7300
Facsimile: (07) 3209 3611

PERTH:
Unit 10, 305 Victoria Road
Malaga, W.A. 6090
Telephone: (08) 9207 9300
Facsimile: (08) 9248 9543