



Consolidated Alloys Fusible Alloys

CA Group

Chemwatch: 6511-17

Version No: 5.1.1.1

Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 3

Issue Date: 27/05/2013

Print Date: 03/04/2017

S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Consolidated Alloys Fusible Alloys
Synonyms	Fusible Alloys, Low Melting Alloys
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Fuses, proof cast testing, lens grinding, tube bending, low temperature soldering, radiation shielding.
--------------------------	---

Details of the supplier of the safety data sheet

Registered company name	CA Group
Address	32 Industrial Avenue Thomastown VIC 3074 Australia
Telephone	+61 3 9359 5811
Fax	+61 3 9359 4076
Website	www.cagroup.com.au
Email	jmarchese@cagroup.com.au

Emergency telephone number

Association / Organisation	(03) 8301 7100
Emergency telephone numbers	(03) 8301 7107 (Business hours 9am – 5pm)
Other emergency telephone numbers	0428 904 506 (After Hours)

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

CHEMWATCH HAZARD RATINGS

	Min	Max
Flammability	0	
Toxicity	2	
Body Contact	2	
Reactivity	0	
Chronic	3	

0 = Minimum
1 = Low
2 = Moderate
3 = High
4 = Extreme

Poisons Schedule	Not Applicable
Classification [1]	Acute Toxicity (Oral) Category 4, Acute Toxicity (Dermal) Category 4, Acute Toxicity (Inhalation) Category 4, Specific target organ toxicity - repeated exposure Category 2
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI

Label elements

GHS label elements	 
--------------------	---

SIGNAL WORD	WARNING
-------------	----------------

Hazard statement(s)

H302	Harmful if swallowed.
H312	Harmful in contact with skin.

Continued...

Consolidated Alloys Fusible Alloys

H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary statement(s) Prevention

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement(s) Response

P363	Wash contaminated clothing before reuse.
P301+P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P330	Rinse mouth.

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

P501	Dispose of contents/container in accordance with local regulations.
-------------	---

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
7440-31-5	NotSpec.	<u>tin</u>
7439-92-1	NotSpec.	<u>lead</u>
7440-69-9	NotSpec.	<u>bismuth</u>
7440-74-6	NotSpec.	<u>indium</u>
7440-36-0	NotSpec.	<u>antimony</u>
7440-43-9	NotSpec.	<u>cadmium</u>
7440-22-4	NotSpec.	<u>silver</u>

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	▶ DO NOT attempt to remove particles attached to or embedded in eye . ▶ Lay victim down, on stretcher if available and pad BOTH eyes, make sure dressing does not press on the injured eye by placing thick pads under dressing, above and below the eye. ▶ Seek urgent medical assistance, or transport to hospital.
Skin Contact	If skin or hair contact occurs: ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation. In case of burns: ▶ Quickly immerse affected area in cold running water for 10 to 15 minutes. ▶ Bandage lightly with a sterile dressing. Treat for shock if required. ▶ Lay patient down. Keep warm and rested. ▶ Transport to hospital, or doctor.
Inhalation	▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area. ▶ Other measures are usually unnecessary.
Ingestion	Not considered a normal route of entry. If poisoning occurs, contact a doctor or Poisons Information Centre.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Copper, magnesium, aluminium, antimony, iron, manganese, nickel, zinc (and their compounds) in welding, brazing, galvanising or smelting operations all give rise to thermally produced particulates of smaller dimension than may be produced if the metals are divided mechanically. Where insufficient ventilation or respiratory protection is available these particulates may produce "metal fume fever" in workers from an acute or long term exposure.

- ▶ Onset occurs in 4-6 hours generally on the evening following exposure. Tolerance develops in workers but may be lost over the weekend. (Monday Morning Fever)
- ▶ Pulmonary function tests may indicate reduced lung volumes, small airway obstruction and decreased carbon monoxide diffusing capacity but these abnormalities resolve after several months.
- ▶ Although mildly elevated urinary levels of heavy metal may occur they do not correlate with clinical effects.
- ▶ The general approach to treatment is recognition of the disease, supportive care and prevention of exposure.
- ▶ Seriously symptomatic patients should receive chest x-rays, have arterial blood gases determined and be observed for the development of tracheobronchitis and pulmonary edema.

Consolidated Alloys Fusible Alloys

- ▶ Gastric acids solubilise lead and its salts and lead absorption occurs in the small bowel.
- ▶ Particles of less than 1 µm diameter are substantially absorbed by the alveoli following inhalation.
- ▶ Lead is distributed to the red blood cells and has a half-life of 35 days. It is subsequently redistributed to soft tissue & bone-stores or eliminated. The kidney accounts for 75% of daily lead loss; integumentary and alimentary losses account for the remainder.
- ▶ Neurasthenic symptoms are the most common symptoms of intoxication. Lead toxicity produces a classic motor neuropathy. Acute encephalopathy appears infrequently in adults. Diazepam is the best drug for seizures.
- ▶ Whole-blood lead is the best measure of recent exposure; free erythrocyte protoporphyrin (FEP) provides the best screening for chronic exposure. Obvious clinical symptoms occur in adults when whole-blood lead exceeds 80 µg/dL.
- ▶ British Anti-Lewisite is an effective antidote and enhances faecal and urinary excretion of lead. The onset of action of BAL is about 30 minutes and most of the chelated metal complex is excreted in 4-6 hours, primarily in the bile. Adverse reaction appears in up to 50% of patients given BAL in doses exceeding 5 mg/kg. CaNa2EDTA has also been used alone or in concert with BAL as an antidote. D-penicillamine is the usual oral agent for mobilisation of bone lead; its use in the treatment of lead poisoning remains investigational. 2,3-dimercapto-1-propanesulfonic acid (DMPS) and dimercaptosuccinic acid (DMSA) are water soluble analogues of BAL and their effectiveness is undergoing review. As a rule, stop BAL if lead decreases below 50 µg/dL; stop CaNa2EDTA if blood lead decreases below 40 µg/dL or urinary lead drops below 2 mg/24hrs.

[Ellenhorn & Barceloux: Medical Toxicology]

BIOLOGICAL EXPOSURE INDEX - BEI

These represent the determinants observed in specimens collected from a healthy worker who has been exposed at the Exposure Standard (ES or TLV):

Determinant	Index	Sampling Time	Comments
1. Lead in blood	30 µg/100 ml	Not Critical	
2. Lead in urine	150 µg/gm creatinine	Not Critical	B
3. Zinc protoporphyrin in blood	250 µg/100 ml erythrocytes OR 100 µg/100 ml blood	After 1 month exposure	B

B: Background levels occur in specimens collected from subjects **NOT** exposed.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- ▶ There is no restriction on the type of extinguisher which may be used.
- ▶ Use extinguishing media suitable for surrounding area.
- ▶ **Do NOT direct a solid stream of water or foam into burning molten material; this may cause spattering and spread the fire.**

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.
-----------------------------	-------------

Advice for firefighters

Fire Fighting	▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear breathing apparatus plus protective gloves in the event of a fire. ▶ Prevent, by any means available, spillage from entering drains or water courses. ▶ Use fire fighting procedures suitable for surrounding area. ▶ DO NOT approach containers suspected to be hot. ▶ Cool fire exposed containers with water spray from a protected location. ▶ If safe to do so, remove containers from path of fire. Slight hazard when exposed to heat, flame and oxidisers.
Fire/Explosion Hazard	▶ Non combustible. ▶ Not considered a significant fire risk, however containers may burn. May emit poisonous fumes.
HAZCHEM	Not Applicable

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	▶ Clean up all spills immediately. ▶ Secure load if safe to do so. ▶ Bundle/collect recoverable product. ▶ Collect remaining material in containers with covers for disposal.
Major Spills	If molten: ▶ Contain the flow using dry sand or salt flux as a dam. ▶ All tooling (e.g., shovels or hand tools) and containers which come in contact with molten metal must be preheated or specially coated, rust free and approved for such use. ▶ Allow the spill to cool before remelting scrap. ▶ Minor hazard. ▶ Clear area of personnel. ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear physical protective gloves e.g. Leather. ▶ Contain spill/secure load if safe to do so. ▶ Bundle/collect recoverable product and label for recycling. ▶ Collect remaining product and place in appropriate containers for disposal.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

Consolidated Alloys Fusible Alloys

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	- Avoid all personal contact, including inhalation. - Wear protective clothing when risk of exposure occurs. - Use in a well-ventilated area. - Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. DO NOT allow material to contact humans, exposed food or food utensils. - Avoid contact with incompatible materials.
Other information	Store away from incompatible materials.

Conditions for safe storage, including any incompatibilities

Suitable container	- Check that containers are clearly labelled - Packaging as recommended by manufacturer.
Storage incompatibility	Avoid storage with oxidisers Avoid strong acids, acid chlorides, acid anhydrides and chloroformates.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	tin	Tin, metal	2 mg/m ³	Not Available	Not Available	Not Available
Australia Exposure Standards	lead	Lead, inorganic dusts & fumes (as Pb)	0.15 mg/m ³	Not Available	Not Available	Not Available
Australia Exposure Standards	lead	Cadmium and compounds (as Cd)	0.01 mg/m ³	Not Available	Not Available	Not Available
Australia Exposure Standards	indium	Indium & compounds (as In)	0.1 mg/m ³	Not Available	Not Available	Not Available
Australia Exposure Standards	indium	Fume (thermally generated) (respirable dust)	2 mg/m ³	Not Available	Not Available	Not Available
Australia Exposure Standards	antimony	Antimony & compounds (as Sb)	0.5 mg/m ³	Not Available	Not Available	Not Available
Australia Exposure Standards	cadmium	Cadmium and compounds (as Cd)	0.01 mg/m ³	Not Available	Not Available	Not Available
Australia Exposure Standards	silver	Silver, metal	0.1 mg/m ³	Not Available	Not Available	Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
tin	Tin	6 mg/m ³	67 mg/m ³	400 mg/m ³
lead	Lead	0.15 mg/m ³	120 mg/m ³	700 mg/m ³
bismuth	Bismuth	15 mg/m ³	170 mg/m ³	990 mg/m ³
indium	Indium	0.3 mg/m ³	3.3 mg/m ³	20 mg/m ³
antimony	Antimony	1.5 mg/m ³	13 mg/m ³	80 mg/m ³
cadmium	Cadmium	Not Available	Not Available	Not Available
silver	Silver	0.3 mg/m ³	170 mg/m ³	990 mg/m ³

Ingredient	Original IDLH	Revised IDLH
tin	Unknown mg/m ³ / 400 mg/m ³ / Unknown ppm	25 mg/m ³ / 100 mg/m ³
lead	700 mg/m ³	100 mg/m ³
bismuth	Not Available	Not Available
indium	Not Available	Not Available
antimony	80 mg/m ³	50 mg/m ³
cadmium	50 mg/m ³ / 9 mg/m ³	9 mg/m ³ / 9 [Unch] mg/m ³
silver	N.E. mg/m ³ / Unknown mg/m ³ / N.E. ppm / Unknown ppm	10 mg/m ³ / 1 mg/m ³

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. If risk of inhalation or overexposure exists, wear SAA approved respirator or work in fume hood.
----------------------------------	---

Consolidated Alloys Fusible Alloys

Personal protection	   
Eye and face protection	▶ Safety glasses with side shields; or as required, ▶ Chemical goggles. ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly.
Skin protection	See Hand protection below
Hands/feet protection	Wear physical protective gloves, e.g. leather Wear safety footwear.
Body protection	See Other protection below
Other protection	▶ Overalls. ▶ Eyewash unit. Aprons, sleeves, shoulder covers, leggings or spats of pliable flame resistant leather or other suitable materials may also be required in positions where these areas of the body will encounter hot metal.
Thermal hazards	Not Available

Respiratory protection

- ▶ Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
- ▶ The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
- ▶ Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.
- ▶ Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.
- ▶ Use approved positive flow mask if significant quantities of dust becomes airborne.
- ▶ Try to avoid creating dust conditions.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Silver/grey dull solid; insoluble in water.		
Physical state	Manufactured	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Applicable
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Applicable	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Applicable
Vapour pressure (kPa)	Not Applicable	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution (1%)	Not Applicable
Vapour density (Air = 1)	Not Applicable	VOC g/L	Not Applicable

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

Consolidated Alloys Fusible Alloys

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	The inhalation of small particles of metal oxide results in sudden thirst, a sweet, metallic foul taste, throat irritation, cough, dry mucous membranes, tiredness and general unwellness. Headache, nausea and vomiting, fever or chills, restlessness, sweating, diarrhoea, excessive urination and prostration may also occur. Lead fume is toxic and acts as a cumulative poison. Regular blood testing should be considered for workers who are regularly exposed.
Ingestion	Considered an unlikely route of entry in commercial/industrial environments Not normally a hazard due to physical form of product.
Skin Contact	Skin contact does not normally present a hazard, though it is always possible that occasionally individuals may be found who react to substances usually regarded as inert. Molten material is capable of causing burns.
Eye	Fumes from welding/brazing operations may be irritating to the eyes.
Chronic	Principal routes of exposure include accidental contact with the molten metal and inhalation of fume arising as a consequence of the action of the flame on the rod / wire. Although fume generation rates are generally low, excessive heating of the material, well above its quoted melting point, may result in over-exposure. Metallic dusts generated by the industrial process give rise to a number of potential health problems. The larger particles, above 5 micron, are nose and throat irritants. Lead, in large amounts, can affect the blood, nervous system, heart, glands, immune system and digestive system. Anaemia may occur. Chronic exposure to tin dusts and fume can result in substantial amounts being deposited in the lungs and result in reduced lung function and difficulty breathing. Chronic bismuth poisoning causes decreased appetite, weakness, rheumatic pain, diarrhoea, fever, foul breath, gum and skin inflammation. Even after exposure ceases there may be a blue line ("bismuth line") on the gums years later. Chronic indium intoxication leads to weight loss, poor growth and extensive necrotic damage to the liver and kidneys. Indium can impede protein synthesis, thereby affecting numerous essential physiological processes, including detoxification of organic cancer causing substances. Intravenous indium chloride may be toxic to the kidney and liver. Damage to the brain, heart, adrenals, spleen and blood may also result from chronic exposures. Repeated or prolonged exposure to antimony and its compounds may produce inflammation of the mouth cavity, dry throat, metallic taste, gum infection, perforation of the nasal septum and throat, laryngitis, headache, difficulty breathing, indigestion, nausea, vomiting, diarrhoea, loss of appetite, anaemia, weight loss, tightness and pain in the chest, sleeplessness, muscular pain and weakness, dizziness, pharyngitis, bronchitis and pneumonia. Degenerative changes of the liver and kidney may occur. Chronic cadmium poisoning causes softening of the bones, reduced bone density, kidney stones and increased blood pressure. There may be cardiovascular disease and a yellow ring in the tooth structure.

Consolidated Alloys Fusible Alloys	TOXICITY	IRRITATION
	Not Available	Not Available
tin	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg ^[1] Oral (rat) LD50: >2000 mg/kg ^[1]	Not Available
lead	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg ^[1] Inhalation (rat) LC50: >5.05 mg/l/4hr ^[1] Oral (rat) LD50: >2000 mg/kg ^[1]	Not Available
bismuth	TOXICITY	IRRITATION
	Oral (rat) LD50: 2000 mg/kg ^[1]	Not Available
indium	TOXICITY	IRRITATION
	Not Available	Not Available
antimony	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >8000 mg/kg ^[1] Oral (rat) LD50: 100 mg/kg ^[2]	Not Available
cadmium	TOXICITY	IRRITATION
	Inhalation (monkey) LC50: 0.03 mg/L15 min ^[1]	Not Available
	Inhalation (monkey) LC50: 0.0467 mg/L15 min ^[1]	
	Inhalation (monkey) LC50: 0.204 mg/L15 min ^[1]	
	Inhalation (monkey) LC50: 0.23 mg/L15 min ^[1]	
	Inhalation (monkey) LC50: 0.94 mg/L15 min ^[1]	
	Inhalation (mouse) LC50: >0.00902 mg/L15 min ^[1]	
	Inhalation (rabbit) LC50: >0.0224 mg/L15 min ^[1]	
	Inhalation (rat) LC50: 0.025 mg/L/30m ^[2] Oral (rat) LD50: >63-<259 mg/kg ^[1]	

Consolidated Alloys Fusible Alloys

silver	TOXICITY	IRRITATION
	Oral (rat) LD50: >2000 mg/kg ^[1]	Not Available

Legend: 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

LEAD	WARNING: Lead is a cumulative poison and has the potential to cause abortion and intellectual impairment to unborn children of pregnant workers.		
TIN & INDIUM	No significant acute toxicological data identified in literature search.		
Acute Toxicity	✓	Carcinogenicity	⊘
Skin Irritation/Corrosion	⊘	Reproductivity	⊘
Serious Eye Damage/Irritation	⊘	STOT - Single Exposure	⊘
Respiratory or Skin sensitisation	⊘	STOT - Repeated Exposure	✓
Mutagenicity	⊘	Aspiration Hazard	⊘

Legend: ✗ – Data available but does not fill the criteria for classification
 ✓ – Data available to make classification
 ⊘ – Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
tin	LC50	96	Fish	>0.0124mg/L	2
tin	EC50	48	Crustacea	0.00018mg/L	5
tin	EC50	72	Algae or other aquatic plants	>0.0192mg/L	2
tin	EC50	72	Algae or other aquatic plants	>0.0192mg/L	2
tin	NOEC	168	Crustacea	<0.005mg/L	2
lead	LC50	96	Fish	0.0079mg/L	2
lead	EC50	48	Crustacea	0.029mg/L	2
lead	EC50	72	Algae or other aquatic plants	0.0205mg/L	2
lead	BCFD	8	Fish	4.324mg/L	4
lead	EC50	48	Algae or other aquatic plants	0.0217mg/L	2
lead	NOEC	672	Fish	0.00003mg/L	4
antimony	LC50	96	Fish	0.93mg/L	2
antimony	EC50	48	Crustacea	1mg/L	2
antimony	EC50	72	Algae or other aquatic plants	>2.4mg/L	2
antimony	EC50	96	Crustacea	0.5mg/L	2
antimony	NOEC	720	Fish	>0.0075mg/L	2
cadmium	LC50	96	Fish	0.001mg/L	4
cadmium	EC50	48	Crustacea	0.0033mg/L	5
cadmium	EC50	72	Algae or other aquatic plants	0.018mg/L	2
cadmium	BCF	960	Fish	500mg/L	4
cadmium	EC50	336	Crustacea	0.00065mg/L	5
cadmium	NOEC	168	Fish	0.00001821mg/L	4
silver	LC50	96	Fish	0.00148mg/L	2
silver	EC50	48	Crustacea	0.00024mg/L	4
silver	EC50	96	Algae or other aquatic plants	0.001628837mg/L	4
silver	BCF	336	Crustacea	0.02mg/L	4
silver	EC50	48	Crustacea	0.00024mg/L	4
silver	NOEC	480	Crustacea	0.00031mg/L	2

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

Bioaccumulative potential

Continued...

Consolidated Alloys Fusible Alloys

Ingredient	Bioaccumulation
	No Data available for all ingredients

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	▶ Recycle wherever possible or consult manufacturer for recycling options. ▶ Consult State Land Waste Management Authority for disposal. ▶ Bury residue in an authorised landfill. ▶ Recycle containers if possible, or dispose of in an authorised landfill.
------------------------------	--

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

TIN(7440-31-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards	Australia Inventory of Chemical Substances (AICS)
Australia Hazardous Substances Information System - Consolidated Lists	

LEAD(7439-92-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards	Australia Inventory of Chemical Substances (AICS)
Australia Hazardous Substances Information System - Consolidated Lists	

BISMUTH(7440-69-9) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)	
---	--

INDIUM(7440-74-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards	Australia Inventory of Chemical Substances (AICS)
Australia Hazardous Substances Information System - Consolidated Lists	

ANTIMONY(7440-36-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards	Australia Inventory of Chemical Substances (AICS)
Australia Hazardous Substances Information System - Consolidated Lists	

CADMIUM(7440-43-9) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards	Australia Inventory of Chemical Substances (AICS)
Australia Hazardous Substances Information System - Consolidated Lists	Australia Work Health and Safety Regulations 2016 - Hazardous chemicals (other than lead) requiring health monitoring

SILVER(7440-22-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards	Australia Inventory of Chemical Substances (AICS)
Australia Hazardous Substances Information System - Consolidated Lists	

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y
Canada - NDSL	N (bismuth; lead; indium; antimony; tin; silver; cadmium)
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	N (bismuth; lead; indium; antimony; tin; silver; cadmium)
Korea - KECI	Y

Continued...

Consolidated Alloys Fusible Alloys

New Zealand - NZIoC	Y
Philippines - PICCS	Y
USA - TSCA	Y
Legend:	<i>Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)</i>

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average
PC – STEL: Permissible Concentration-Short Term Exposure Limit
IARC: International Agency for Research on Cancer
ACGIH: American Conference of Governmental Industrial Hygienists
STEL: Short Term Exposure Limit
TEEL: Temporary Emergency Exposure Limit,
IDLH: Immediately Dangerous to Life or Health Concentrations
OSF: Odour Safety Factor
NOAEL :No Observed Adverse Effect Level
LOAEL: Lowest Observed Adverse Effect Level
TLV: Threshold Limit Value
LOD: Limit Of Detection
OTV: Odour Threshold Value
BCF: BioConcentration Factors
BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.